## **GENIE GR-15 RUNABOUT**





MEASUREMENTS		METRIC	IMPERIAL
Working height maximum*		6.30 m	20 ft 8 in
Platform height maximum		4.47 m	14 ft 8 in
	Platform dimensions (length x width)		
A x B	Standard	0.89 x 0.75 m	2 ft 11 in x 2 ft 6 in
	Standard with extension	1.40 x 0.75 m	4 ft 7 in x 2 ft 6 in
С	Height - stowed	1.62 m	5 ft 4 in
D	Length - stowed	1.35 m	4 ft 5 in
Е	Width	0.75 m	2 ft 6 in
F	Ground clearance - centre	6 cm	2 in


PRODUCTIVITY		
Platform capacity	227 kg	500 lb
Slide-out platform extension deck capacity	113 kg	249 lb
Maximum number of persons - indoor / outdoor use	1/0	1/0
Maximum wind speed	0 km/h	0 mph
Drive speed - stowed	4.0 km/h	2.4 mph
Drive speed - raised	0.8 km/h	0.49 mph
Gradeability**	30%	16.70°
Inside turning radius	zero	zero
Outside turning radius	0.79 m	2 ft 7 in
Raise / lower speed	21 / 19 sec	21 / 19 sec
Controls	proportional	proportional
Tyres - solid non-marking	25 x 8 x 2.5 cm	10 x 3 x 1 in
Wheel load maximum***	606 kg	1,336 lb
Tyre contact pressure***	14.4 kg/cm <sup>2</sup> (1,418 kPa)	205.7 psi
Occupied floor pressure***	1,210 kg/m²(11.87 kPa)	248 psf

POWER				
Power source 24 V (four 6 V 225 Ah batter				
Hydraulic system capacity	8.33 L 2.20 ga	l lqd		

WEIGHT****		
	1,011 kg	2, 228 lb







<sup>\*</sup>The metric equivalent of working height adds 2 m to platform height. Imperial adds 6 ft to platform height.

<sup>\*\*</sup>Gradeability applies to driving on slopes. See operator's manual for details regarding slope rating.

\*\*Floor loading information is approximate. It should be used only with adequate safety factors.

\*\*\*\*Weight will vary depending on options.